

KX-NCS8100 IP Softphone

PC Based IP Softphone

24 programmable keys

One-Touch Recording

Message/Ringer Indication

Copy and Paste to Dial from any Application

IP Telephony over Secure Broadband

IP Telephony over Secure Broadband



IP Softphone for Microsoft Windows

Features

| | |
|---|--|
| LCD Display | Alphanumeric Display (6 Lines x 24 Characters) |
| Feature Access Keys for Display | 4.0 |
| Programmable CO Keys | 24.0 |
| Direct Station Selection (DSS) Keys with Busy Lamp Field (BLF) | yes |
| Navigator Key | yes |
| Message / Ringer Lamp | yes |
| Call Forward/Do Not Disturb | yes |
| Redial | yes |
| Flash / Recall | yes |
| Hold | yes |
| Auto Dial (System Speed Dialing) | yes |
| Transfer | yes |
| Conference | yes |
| Intercom | yes |
| Message | yes |
| Pause | yes |
| Answer Key | yes |
| Release Key | yes |

| | |
|--|-------------|
| Auto Answer/Mute | yes |
| Record (Enhanced feature) | yes |
| Speakerphone | yes |
| Off Hook Monitor | yes |
| SP-Phone (Monitor) Volume Control | 12 Levels |
| Handset Volume Control | 4 Levels |
| Ringer Volume Control | 4 Levels |
| Paging Receive | yes |
| Station Speed Dial | 100 Numbers |
| License | 1 User |

System Requirements (PC)

| | |
|------------------------------|--|
| Operating System | Windows XP SP2 |
| CPU | Pentium M 1.86GHz (or higher) |
| RAM | 512 MB (or higher) |
| Hard Drive disk space | 250MB (or higher) |
| LAN (Ethernet) | 100 Base-T (or higher) |
| Display | XGA 1024 x 768 |
| Broadband | Business grade xDSL (recommended for remote users) |
| Firewall | Tested with: XP SP2 Firewall, Zone Alarm v6.5, Norton Personal, Firewall v2006, McAfee Personal Firewall v7.0, Sygate v5.6 |
| VPN | Tested over standard hardware based IPSec VPN |
| Bandwidth | Fixed 100KB per call |
| Peripheral Devices | Sound Card, Speaker, Microphone, CD-ROM drive |
| PBX | KX-TDA100/200 PMPR software file version 3.0 or later KX-TDA600 PLMPR software file version 2.2 or later |
| IP extension card | Part Number: KX-TDA0470 with latest firmware |
| CODEC | G.711 (20msec packetisation) |